



Rust Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 28/11/2025 Revision date: 12/11/2025 Supersedes version of: 27/08/2024 Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Rust Seal
Product code : BDS002630BU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Use of the substance/mixture : Anti Corrosion Products

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V.
Touwslagerstraat 1
9240 Zele
Belgium
T +32(0)52/45.60.11, F +32(0)52/45.00.34
hse@crcind.com, www.crcind.com

1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11
Office hours: 9-17h CET

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment – Chronic Hazard, H412
Category 3
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : -

Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P102 - Keep out of reach of children.
P273 - Avoid release to the environment.
P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements : EUH208 - Contains 3-aminopropyltriethoxysilane (919-30-2). May produce an allergic reaction.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Rust Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dipropylene glycol methyl ether substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011-60	< 2.5	Not classified
Amines, tallow alkyl, ethoxylated	CAS-No.: 61791-26-2	0,25 - <1	Acute Tox. 4 (Oral), H302 (ATE=300 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
3-aminopropyltriethoxysilane	CAS-No.: 919-30-2 EC-No.: 213-048-4 EC Index-No.: 612-108-00-0 REACH-no: 01-2119480479-24	0,1 - <1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.
First-aid measures after skin contact	: Wash skin with plenty of water. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: During fire, gases hazardous to health may be formed.
--	---

5.3. Advice for firefighters

Firefighting instructions	: Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

Rust Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment : Wear appropriate protective equipment and clothing during clean-up.
Emergency procedures : Ventilate spillage area.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.
Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wear personal protective equipment. Ensure good ventilation of the work station. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container closed when not in use.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Dipropylene glycol methyl ether (34590-94-8)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	(2-Methoxymethylethoxy)-propanol
IOEL TWA	308 mg/m ³
	50 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

Rust Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol methyl ether (34590-94-8)	
United Kingdom - Occupational Exposure Limits	
Local name	(2-methoxymethylethoxy) propanol
WEL TWA (OEL TWA)	308 mg/m ³
	50 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

DNEL and PNEC

Dipropylene glycol methyl ether (34590-94-8)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	283 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	308 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	36 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	37.2 mg/m ³
Long-term - systemic effects, dermal	121 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	19 mg/l
PNEC aqua (marine water)	1.9 mg/l
PNEC aqua (intermittent, freshwater)	190 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	70.2 mg/kg dwt
PNEC sediment (marine water)	7.02 mg/kg dwt
PNEC (Soil)	
PNEC soil	2.74 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	4168 mg/l
3-aminopropyltriethoxysilane (919-30-2)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	3.5 mg/m ³
Long-term - systemic effects, dermal	1 mg/kg bodyweight/day

Rust Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protection equipment

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended. Layer thickness : > 0,10 mm.

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: A

Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Black.
Appearance	: Viscous liquid.
Odour	: Neutral.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 100 °C
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Not available
pH	: 8 – 9
Viscosity, kinematic	: 90 – 100 Krebs Unit
Solubility	: soluble in water.

Rust Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1.03 g/cm ³
Relative density	: 1.03
Relative vapour density at 20°C	: > 1
Particle characteristics	: Not applicable

9.2. Additional Regulatory Information

Other safety characteristics

VOC content : 31 g/l (Cat. A(i) VOC max 140 g/L)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Avoid temperatures exceeding the flash point.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Dipropylene glycol methyl ether (34590-94-8)	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	9510 mg/kg bodyweight
Amines, tallow alkyl, ethoxylated (61791-26-2)	
LD50 oral rat	300 – 2000 mg/kg
LD50 dermal rat	> 10000 mg/kg
3-aminopropyltriethoxysilane (919-30-2)	
LD50 dermal rabbit	4290 mg/kg
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: 8 – 9
Dipropylene glycol methyl ether (34590-94-8)	
Skin corrosion/irritation	Not classified (Based on available data, the classification criteria are not met)

Rust Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Amines, tallow alkyl, ethoxylated (61791-26-2)	
Skin corrosion/irritation	Causes skin irritation.
3-aminopropyltriethoxysilane (919-30-2)	
Skin corrosion/irritation	Causes severe skin burns.
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: 8 – 9
Dipropylene glycol methyl ether (34590-94-8)	
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met)
Amines, tallow alkyl, ethoxylated (61791-26-2)	
Serious eye damage/irritation	Causes serious eye damage.
3-aminopropyltriethoxysilane (919-30-2)	
Serious eye damage/irritation	Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
3-aminopropyltriethoxysilane (919-30-2)	
LOAEL (oral, rat, 90 days)	600 mg/kg bodyweight
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Rust Seal	
Viscosity, kinematic	90 – 100 Krebs Unit

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %
--	--

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Dipropylene glycol methyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l
EC50 - Crustacea [1]	1919 mg/l Daphnia magna (Water flea)
EC50 96h - Algae [1]	> 969 mg/l
NOEC (chronic)	≥ 0.5 mg/l Daphnia magna (22 d)

Rust Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol methyl ether (34590-94-8)

NOEC chronic algae	> 969 mg/l
--------------------	------------

Amines, tallow alkyl, ethoxylated (61791-26-2)

LC50 - Fish [1]	0.13 mg/l Oncorhynchus mykiss
-----------------	-------------------------------

EC50 - Crustacea [1]	0.17 mg/l Daphnia magna
----------------------	-------------------------

3-aminopropyltriethoxysilane (919-30-2)

LC50 - Fish [1]	> 934 mg/l Danio rerio
-----------------	------------------------

EC50 - Crustacea [1]	331 mg/l Daphnia magna
----------------------	------------------------

EC50 72h - Algae [1]	603 mg/l
----------------------	----------

12.2. Persistence and degradability

Rust Seal

Persistence and degradability	Not established. No data is available on the degradability of this product.
-------------------------------	---

12.3. Bioaccumulative potential

Rust Seal

Partition coefficient n-octanol/water (Log Kow)	Not applicable
---	----------------

3-aminopropyltriethoxysilane (919-30-2)

Partition coefficient n-octanol/water (Log Pow)	-2.9
---	------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Rust Seal

Results of PBT assessment	Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII
---------------------------	--

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Rust Seal

Additional Regulatory Information	No other effects known
-----------------------------------	------------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW, EC 2000/532) : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

Rust Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
14.2. UN proper shipping name				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.3. Transport hazard class(es)				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.4. Packing group				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.5. Environmental hazards				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

Inland waterway transport

Not regulated.

Rail transport

Not regulated.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Rust Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 31 g/l (Cat. A(i) VOC max 140 g/L)

Seveso Directive (Disaster Risk Reduction)

Seveso Additional information : Directive 2012/18/EU (SEVESO III)
Not subject to Annex I

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
8.2	Hand protection	Modified Thickness
15	Seveso Additional information	Added
16	Data sources	Added

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association

Rust Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Data sources

: REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Rust Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains 3-aminopropyltriethoxysilane (919-30-2). May produce an allergic reaction.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aquatic Chronic 3	H412	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.